

MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE

This product contains crystalline silica, which is classified as a hazardous substance according to the criteria provided by the Australian Safety and Compensation Council.

Address: c/- JKR Lawyers (QLD) Pty. Ltd.
Level 2, 168 Edward Street
BRISBANE QLD 4000

Telephone: 0447 888 018

Section 1. Chemical Products and Company Identification

Product Names:

Mineral Dust
Mineral Mulch 4
Mineral Mulch 6
Mineral Mulch 8
Mineral Mulch 12
Mineral Mulch 14

Use: Soil amendment, soil ameliorant, soil conditioner for agriculture. Soil treatment for contaminated soils.

Manufacturer: ShiftWaste Pty. Ltd. T/A Mineral Mulch c/- JKR Lawyers (QLD) Pty. Ltd. Level 2, 168 Edward Street, BRISBANE, QLD, 4000.

Effective date: July 1, 2013

NOTE: As of date of the preparation of this document, the information contained herein is believed to be accurate.

Substance Name	CAS Number	UN Number	EINECS Number	Proportion (by weight)
Crystalline Silica (Quartz)	14808-60-7	Not a hazardous material for shipping purposes	238-878-4	10 – 30%
Calcium Silicate (Hydrate)	65997-15-1	Not a hazardous material for shipping purposes	266-043-4	10-60%
Cellulose	9004-34-6	Not a hazardous material for shipping purposes	232-674-9	< 10%
Other non-hazardous ingredients				< 10%

Note: This product does not contain asbestos or asbestiform fragments. Cellulose comes from wood pulp.

Section 2. Hazards Identification

Risk Phrases: Irritating to respiratory system
Harmful: danger of serious damage to health by prolonged exposure through inhalation

Safety Phrases: Do not breathe dust.

Emergency Overview: Not explosive, not a fire hazard.

Primary Routes of Entry and Potential Health Effects:

Inhalation:

Acute Effects – Dust may cause irritation of the nose, throat, and airways, resulting in coughing and sneezing. Certain susceptible individuals may experience wheezing (spasms of the bronchial airways) on inhaling dust.

Chronic Effects – Repeated and prolonged overexposures to dust containing crystalline silica can cause silicosis (scarring of the lung) and increases in the risk of bronchitis, tuberculosis, lung cancer, renal disease and scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs). Some studies suggest that cigarette smoking increases the risk of silicosis, bronchitis and lung cancer in persons also exposed to crystalline silica.

Acute Silicosis – a sub-chronic disease associated with acute, massive silica exposure, is a rapidly progressive, incurable lung disease that is typically fatal. Symptoms include, but are not limited to, shortness of breath, cough, fever, weight loss and chest pain. Such exposure may cause pneumoconiosis and pulmonary fibrosis.

Ingestion:

Unlikely under normal conditions of use, but swallowing the dust from this product may result in irritation or damage to the mouth and gastrointestinal tract due to alkalinity of dust.

Eye:

Dust may irritate the eyes from mechanical abrasion causing watering and redness.

Skin:

Dust may cause irritation of the skin from friction but cannot be absorbed through intact skin.

Medical conditions generally aggravated by exposure:

Pulmonary function may be reduced by inhalation of respirable crystalline silica and/or cellulose. If lung scarring occurs, such scarring could aggravate other lung conditions such as asthma, emphysema, pneumonia or restrictive lung diseases. Lung scarring from crystalline silica may also increase risks to pulmonary tuberculosis.

Smoking:

Some studies suggest that cigarette smoking increases the risk of occupational respiratory diseases, including silica-related respiratory diseases.

Carcinogenicity:

The International Agency for the Research on Cancer (IARC) has classified crystalline silica inhaled in the forms of quartz or cristobalite from occupational sources as carcinogenic to humans.

LD50:

Silicon Dioxide: Rat oral >22,500 mg/kg

Mouse oral >10,500 mg/kg

Section 3. Hazardous Ingredients / Identity Information

Substance Name	CAS Number	UN Number	EINECS Number	Proportion (by weight)
Crystalline Silica (Quartz)	14808-60-7	Not a hazardous material for shipping purposes	238-878-4	10 – 30%
Calcium Silicate (Hydrate)	65997-15-1	Not a hazardous material for shipping purposes	266-043-4	10-60%
Cellulose	9004-34-6	Not a hazardous material for shipping purposes	232-674-9	< 10%

Section 4. First Aid Measures

Signs and symptoms of over exposure: Breathlessness, wheezing, cough, sputum production

First Aid:

Swallowed:

If swallowed, dilute by drinking large amounts of water. Do not induce vomiting. Seek medical attention. If unconscious, loosen tight clothing and lay person on his/her left side. Give nothing by mouth to an individual who is not alert and conscious.

Eye Contact:

Remove contact lenses. Flush with running water or saline for at least 15mins. Seek medical attention if redness persists or if visual changes occur.

Skin Contact:

Wash with mild soap and water. Contact physician if irritation persists or later develops.

Inhaled:

Remove to fresh air. If shortness of breath or wheezing develops, seek medical attention.

ADVICE TO DOCTOR: Treat symptomatically.

Section 5. Fire Fighting Measures

Mineral Mulch manufactured products are neither flammable nor explosive. Refer to page 1 for list of Mineral Mulch manufactured products.

- Fire and Explosion Hazard:**
1. Flash Point: Not applicable
 2. Auto-ignition: Not applicable
 3. Non-flammable and non-explosive

Extinguishing Media: This material is not combustible. Appropriate extinguishing media (carbon dioxide, foam, water, or dry chemical) for surrounding fire should be used.

Fire Fighting: Fire fighting personnel should wear normal protective equipment and positive self-contained breathing apparatus.

Section 6. Accidental Release Measures

No special precautions are necessary to pick up product that has been dropped. The following applies to spills or releases of dust during moving or dispersing of the material.

Precautions: Good housekeeping practices are necessary for cleaning up areas where leaks or spills have occurred, dust has accumulated, including leaks and spills. Take measures to either eliminate or minimize the creation of dust. Respirable dust and silica levels should be monitored regularly.

Wherever possible, practices likely to generate dust should be controlled with engineering controls such as local exhaust ventilation, dust suppression with water and containment, enclosures or covers.

Use respiratory protection as described in Section 8.

Cleanup Methods: A fine water spray should be used to suppress dust when sweeping (dry sweeping should not be attempted). Vacuuming with an industrial vacuum cleaner outfitted with a high-efficiency particulate (HEPA) filter, is preferred to sweeping. Waste may be disposed of by landfill in compliance with federal, state and local requirements.

In the event of an accidental release, observe all protection measures set out in this MSDS. Avoid using materials and products that are incompatible with the product. (refer to Section 10)

Section 7. Handling and Storage.

Note: The controls below refer to dust generated by the dispersal and application of the Mineral Mulch products.

Mineral Mulch's recommendation:

Keep exposure to dust as low as possible. Respirable crystalline silica levels should not exceed those specified by the Australian Safety and Compensation Council and identified in this MSDS. Exposure to respirable (fine) silica dust depends on a variety of factors including activity rate, method of handling, environmental conditions and control measures used.

Practices likely to generate dust should be carried out in adequately ventilated areas. The work practices and engineering controls set out in Section 8 should be followed to reduce silica exposures.

Keep away from reactive products. Do not store near food. Beverages and smoking materials. Avoid spilling and creating dust. Maintain appropriate dust controls and handling. Use appropriate respiratory protection during handling as described in Section 8.

Section 8. Exposure Controls and Personal Protection

EXPOSURE STANDARDS:

WORKSAFE AUSTRALIA

Ingredients

Occupational Exposure Standards

Crystalline Silica (Quartz)	0.1 mg/m ³ time-weighted average (TWA) respirable dust
Dust (NOS –not otherwise specified)	10 mg/m ³ TWA as inhalable dust
Calcium Silicate	10mg/m ³ TWA as inhalable dust
Cellulose (paper)	10mg/m ³ TWA as inhalable dust

Where a state or local authority prescribes a lower standard, the lower standard applies.

Personal Protection

Respiratory: When handling products that may generate silica dust: (1) work outdoors whenever possible, (2) wear a properly-fitted approved dust mask or respirator (e.g. P1 or P2) in accordance with applicable government regulations and manufacturers instructions to further limit respirable silica exposures, and (3) warn others in area. Use and maintain respirators in accordance with AS/NZS 1715 & 1716 for particulate respirators. Select respirators based on the level of exposure to crystalline silica. Use respirators that offer protection to the highest concentrations of crystalline silica if actual concentrations are unknown. Comply with all other federal and state law.

Eyes: Dust resistant safety goggles/glasses should be worn. AS/NZS1336 "Recommended Practices for Eye Protection in the Industrial Environment" provides further guidance.

Skin: Loose comfortable clothing should be worn. Direct skin contact with dust and debris should be avoided by wearing long sleeved shirts and long trousers, a cap or hat, and gloves – standard duty leather or equivalent AS2161 "Industrial Safety Gloves and Mittens". Work clothes should be washed regularly.

Engineering Controls:

SOIL APPLICATION

1. Ensure all plant and equipment operators are operating machinery with filtered air-conditioned operator cabs.
2. Ensure spreading is undertaken in appropriate weather conditions i.e. no wind.
3. Ideally apply Mineral Mulch products to damp soil at time of application.
4. Ensure all PPE recommendations are observed.

BLENDING & MIXING

1. Ensure adequate dust suppression is used e.g. water sprays or misting systems.
2. Ensure all blended products are supplied with this MSDS.

Section 9. Physical and Chemical Properties

Appearance and odour:

Mineral Dust: Powder similar in consistency to that of talcum powder, coloured grey through pink.

Mineral Mulch: Flat particles ranging in size from 60 micron through to 14mm (depending on Mineral Mulch in size. Particles are generally no more than 1.5mm thick. Coloured grey through pink.

Vapour Pressure:	Not Relevant	Flash Point:	Not Relevant
Specific Gravity:	Not Relevant	Autoignition Temp:	Not Relevant
Flammability Limits:	Not Relevant	Volatility:	Not Relevant
Boiling Point:	Not Relevant	Solubility in Water:	Not Relevant
Melting Point:	Not Relevant	Evaporation Rate:	Not applicable

Section 10. Stability and Reactivity

Stability: Crystalline silica is stable under ordinary conditions.

Conditions to Avoid: Excessive dust generation during storage and handling.

Materials to Avoid:

Incompatibility: Hydrofluoric acid will dissolve silica and can generate silicone tetrafluoride, a corrosive gas. Contact with strong oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride or oxygen difluoride may cause fires and/or explosions.

Section 11. Toxicological Information

The product is not toxic in its intact form. The following applies to dust that may be generated during land application, or moving dust during cleaning process:

Chronic Effects:

Inhaled:

Repeated and prolonged overexposures to dust containing crystalline silica can cause silicosis (scarring of the lung) and increases the risk of bronchitis, tuberculosis, lung cancer, renal disease and scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs). Some studies suggest that cigarette smoking increases the risk of silicosis, bronchitis, and lung cancer in persons also exposed to crystalline silica. Acute silicosis is a rapidly progressive, incurable lung disease that is typically fatal. Symptoms include, but are not limited to: shortness of breath, cough, fever, weight loss and chest pain. Such exposure may cause pneumoconiosis and pulmonary fibrosis.

The following relates to health effects of cellulose: based on limited animal research, it is possible that repeated chronic inhalation exposure to cellulose fibre dust over time may lead to inflammation and scarring of the lung in humans. Precautions taken for crystalline silica dust will protect against cellulose.

Section 12. Ecological Information

Clean up of the spilled product would not leave any hazardous material that could cause a significant adverse impact. There is a limited amount of ecological data available on crystalline silica, primarily because it is a naturally occurring mineral. An adequate representation of this data is beyond the scope of this document.

Section 13. Disposal Consideration

Dispose of material as inert, non-metallic mineral in conformance with local, state and federal regulations.

Section 14. Transport Information

There is no special requirements for storage and transport.

UN NO:	None Allocated
Dangerous Goods Class:	None Allocated
Hazchem Code:	None Allocated
Poisons Schedule:	None Allocated
Packing Group:	Not Applicable
Label:	Local regulations may apply

Section 15. Regulatory Information

Regulatory information is provided within the relevant sections of this material safety data sheet, as appropriate.

Section 16. Other Information

WARNING

DO NOT BREATHE DUST

Shiftwaste products contain sand, a source of respirable crystalline silica which is considered by some international authorities to be a cause of cancer from some occupational sources. Breathing excessive amounts of respirable silica dust can also cause a disabling and potentially fatal lung disease called silicosis, and has been linked with other diseases. Some studies suggest smoking may increase these risks. During installation or handling: (1) Work in outdoor areas with ample ventilation; (2) Minimise dust when applying to soil through use of spraying and misting systems and ensuring spreading is undertaken on days with little to no wind; (3) Warn others in the immediate area to avoid breathing dust; (4) Wear a properly-fitted, approved dust mask or respirator (e.g, P1 or P2) in accordance with applicable government regulations and manufacturer instructions to further limit respirable silica exposures. During clean-up use HEPA vacuums or wet cleanup methods – never dry sweep.

FAILURE TO ADHERE TO OUR WARNINGS, MATERIAL SAFETY DATA SHEETS, AND INSTALLATION INSTRUCTIONS MAY LEAD TO SERIOUS PERSONAL INJURY OR DEATH.

**Shiftwaste Pty Ltd T/A Mineral Mulch
C/- JKR Lawyers (QLD) Pty. Ltd.
Level 2, 168 Edward Street
BRISBANE QLD 4000
0447 888 018**

This form has been prepared in line with guidelines provided by the Australian Safety and Compensation Council and is offered without any warranty or guarantee of any type. Shiftwaste Pty Ltd cannot control the use of its products, and therefore specifically disclaims liability and responsibility arising from the use, misuse and alteration of its products.

The information contained on this MSDS was produced without independent scientific or medical studies analysing the effects of silica upon human health. The information contained herein is based upon scientific and other data Shiftwaste Pty Ltd believes is valid and reliable and provides the basis for this MSDS. The information contained herein relates only to specific materials listed in the document. It does not address the effects of silica when used in combination with other materials or substances, or when used in other processes. Because conditions of use are beyond the control of Shiftwaste Pty Ltd, the company makes no representations, guarantees or warranties, either express or implied warranties as to the fitness of the product or use, and assume no liability related to the information contained above.

Shiftwaste Pty Ltd requires, as a condition of use of its products, that purchasers comply with all applicable Federal, State, and Local health and safety laws, regulations, orders, requirements, and strictly adhere to all instructions and warnings which accompany the product.